

	Product Code:	<b>440070</b>
	Product Name:	<b>BONDEX DECKING OIL</b>
	Recommended for:	<b>Wooden Decks Outdoor</b>
	Available sizes:	<b>2.50 L - 5.00 L - 20.00 L</b>



<i>Hard wearing</i>	<i>Water repellent</i>	<i>Preserves the original glow of the wood</i>	<i>Coverage: 10-16 m<sup>2</sup>/l</i>	<i>Touch dry: 3-5 hours</i>	<i>Recoatable: 24 hours</i>	<i>Clean tools with white spirit</i>
---------------------	------------------------	--	--	-----------------------------	-----------------------------	--------------------------------------

## 1. Product Description

1.1	<b>Product Type:</b>	Special oil for the care of wooden decks and terraces.
1.2	<b>Manufacturer:</b>	Dyrup A/S - Gladsaxevej 300 - 2860 - Søborg - Denmark Phone: +45 39 57 93 00 - www.dyrup.com
1.3	<b>Where to use:</b>	Wooden decks outdoors.
1.4	<b>Special Qualities:</b>	Hard wearing. The oil gives a water repellent effect. The original glow of the wood is preserved. Extra long durability. Protection against the weather.
1.5	<b>Colour Range:</b>	• 668 Red Mahogany • 710 Pine • 722 Oak • 725 Palisander • 729 Teak • 731 Nut Brown • 900 Clear
1.6	<b>Form Supplied:</b>	Ready to use.
1.7	<b>Test Reports / Certificates:</b>	Not available at present.

## 2. Composition

2.1	<b>Binder:</b>	Alkyd.
2.2	<b>Solvents:</b>	White Spirit.
2.3	<b>VOC-content:</b>	Not relevant for this product.
2.4	<b>Pigments:</b>	Organic and inorganic pigments.

2.5	<b>Active Ingredients:</b>	None.
-----	----------------------------	-------

2.6	<b>Additives:</b>	Not relevant for this product.
-----	-------------------	--------------------------------

### 3. Technical Data

3.1	<b>Specific Gravity:</b>	Approx. 0.9 kg/l.
-----	--------------------------	-------------------

3.2	<b>Viscosity:</b>	>62 sec./ISO cup 6 mm/23°C.
-----	-------------------	-----------------------------

3.3	<b>Flash Point:</b>	62°C, Pensky Martens.
-----	---------------------	-----------------------

3.4	<b>Gloss:</b>	Matt.
-----	---------------	-------

3.5	<b>Solid Content:</b>	Approx. 51,0 W/W%.
-----	-----------------------	--------------------

3.6	<b>Odour</b>	Strong.
-----	--------------	---------

3.7	<b>Coverage:</b>	10-16 m <sup>2</sup> /l, depending on the type of wood and the state of substrate.
-----	------------------	--

3.8	<b>Drying Time:</b>	<u>Touch dry</u> : Approx. 3-5 hours. <u>Recoatable</u> : approx. 24 hours. <u>Through hardening</u> : Approx. 1 week - (at 23°C and standard humidity of 60%).
-----	---------------------	---

3.9	<b>Weather Resistance:</b>	Water repellent.
-----	----------------------------	------------------

3.10	<b>Alkaline Resistance:</b>	
------	-----------------------------	--

3.11	<b>Biocide Effect:</b>	Note relevant for this product.
------	------------------------	---------------------------------

3.12	<b>Thinning:</b>	Do not thin.
------	------------------	--------------

3.13	<b>Storage:</b>	5 years in unopened containers. Store frost-free.
------	-----------------	---

3.14	<b>Shelf Life:</b>	5 years in unopened containers.
------	--------------------	---------------------------------

### 4. Surface & Preparation

4.1	<b>In General:</b>	Stir well before and during application. Keep container firmly closed after use.
-----	--------------------	--

4.2 **Substrate:** The surface must be clean, dry and solid.

4.3 **Humidity:** The wood moisture at the time of the treatment must not exceed 18%.

## 5. Treatment

5.1 **Application Method:** By brush until the wood is saturated

5.1 **Pre treatment:** Previously treated surfaces must be cleaned with a suitable detergent. Rinse with clean water. Decayed wood must be planed down to sound wood.

5.2 **Treatment:** 2 x BONDEX Decking Oil.

5.3 **Renovation of Previously treated Wood:** Maintenance: Approx. Once a year with 1-2 applications of BONDEX Decking Oil.

5.4 **Cleaning of Tools:** Clean tools immediately with white spirit.

## 6. Safety Precautions

6.1 **In General** Common safety rules for work with paints must be observed. Further information is available from our Material Safety Data Sheet.

6.2 **Safety Instructions:**

- Contains Naphta (petroleum), hydrotreated heavy
- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
- Contains 2-Butanonoxime and Cobalt carboxylate. may produce an allergic reaction
- Keep out of the reach of children
- Do not breathe vapour/spray
- Avoid contact with skin
- Do not empty into drains
- If swallowed, seek medical advice immediately and show this container or label or this data sheet
- Avoid release into the environment. Refer to special instructions / safety data sheet
- Rags soaked with the product may cause spontaneous combustion

## 7. Disposal

7.1 **Disposal:** Do not empty into drains or into the environment. Product waste must not be poured into the sewers, water reserves or soil. Empty can may be recycled (check with you local waste disposal site or your local authorities).

*This datasheet is assigned to describe the applicability of BONDÉX Decking Oil in a serious and non-binding way. The technical indications are based on years' of research, but the consumer is hereby not dissuaded to test the product before use. If any doubts, please refer to our agents or technical departments. This Technical Data Sheet replaces all former editions (please refer to the date in the top right hand corner for reference).*